



SYNC UNDER DOOR CAMERA

SPEC SHEET: TACTICAL ELECTRONICS

ELITE CAMERA SYSTEMS



IDENTIFICATION:



FEATURES:



- + **INSERTION PANEL:** 0.26in insertion panel thickness
- + **TWO CAMERAS:** Forward & upward looking cameras
- + **TOGGLE:** Toggle between dual camera views
- + **LOW-LIGHT:** 640x480px color sensor with 16V/lux-sec
- + **INFRARED LEDs:** 4 x 950nm IR LEDs for covert video
- + **HARDWIRE:** Hardwired power for quick deployment



TOGGLE VIDEO

Toggle between forward & upward camera views



ADJUSTABLE LEDs

Toggle LEDs illumination 0% - 50% - 100%



COMPACT DESIGN

Rapid deployment and quick, easy stow away



LOW LIGHT SENSOR

Most sensitive 0.25in sensor on the market

DESCRIPTION:



The SYNC Under Door Camera gives you rapid visual access into rooms or around corners. Featuring two individual cameras located within a 6.6mm/0.26in thick insertion panel, the SYNC UDC provides both forward and upward camera views.

Each camera view is supplemented with covert 950nm Infrared LED illumination for low-light and no-light applications. Simply plug the SYNC Under Door Camera into any Android tablet or mobile device to view video on the TE View mobile app.

Measuring less than 2in wide and 7in long the SYNC Under Door Camera can be easily stowed in a cargo pocket for quick deployment.

TACTICAL ELECTRONICS

DOCUMENT:

SPECIFICATIONS SHEET
OFFICIAL I PROPRIETARY

COPYRIGHT:

© 2024 TACTICAL ELECTRONICS
AND MILITARY SUPPLY, LLC.

NOTICE: PRODUCT INFORMATION &
SPECIFICATIONS ARE SUBJECT TO
CHANGE WITHOUT NOTICE.

1

WEBSITE:

TACTICALELECTRONICS.COM

EMAIL:

GOVSALES@TACTICALELECTRONICS.COM

PHONE:

(+1) 833 / 483 / 1441 • (+1) 918 / 249 / 8326



SYNC UNDER DOOR CAMERA

SPEC SHEET: TACTICAL ELECTRONICS

ELITE CAMERA SYSTEMS



SPECIFICATIONS:

WEIGHT:	14oz	0.4kg
DIMENSIONS:	L 7.0in x W 1.8in x H 0.7in	L 17.8cm x W 4.6cm x H 1.8cm
INSERTION PANEL THICKNESS:	0.260in	6.6mm
POWER SUPPLY:	Mobile Android Device / SWIFT Pole Camera	
HOUSING MATERIAL:	HDPE / 6061-T6 Aluminum	
OPERATING TEMPERATURE:	-4°F to 122°F / -20°C to 50°C	
HARDWARE COMMUNICATION:	Compatible integration with: ATAK / MANET / Mobile devices	
HARDWARE DATA TRANSFER:	USB transfer capable	
HARDWARE CONNECTION:	Push/pull Tactical ODU port and connector	
VIDEO FORMAT:	YUY2 (YUV 4:2:2) UVC video over USB3.1	
CAMERA SENSOR:	2 x 0.25in CMOS Color Digital Image Sensor	
CAMERA RESOLUTION:	640 x 480px @ 30fps	
CAMERA LIGHT SENSITIVITY:	16V/lux-sec	
HORIZONTAL FIELD OF VIEW:	87°	
ILLUMINATION:	2 x 950nm IR LEDs (adjustable toggle: 0%, 50%, 100%)	

TACTICAL ELECTRONICS

DOCUMENT:

SPECIFICATIONS SHEET
OFFICIAL I PROPRIETARY

COPYRIGHT:

© 2024 TACTICAL ELECTRONICS
AND MILITARY SUPPLY, LLC.

NOTICE: PRODUCT INFORMATION &
SPECIFICATIONS ARE SUBJECT TO
CHANGE WITHOUT NOTICE.

2

WEBSITE: TACTICALELECTRONICS.COM

EMAIL: GOVSALES@TACTICALELECTRONICS.COM

PHONE: (+1) 833 / 483 / 1441 • (+1) 918 / 249 / 8326